

Descriptions

This is Silicon Diode in a SOT-23 Plastic Package


Features

- Small signal diode
- Halogen-free product

Applications

High Conductance Ultra Fast Diode.

Equivalent Circuit



Pinning



PIN: See Equivalent Circuit.

Marking

Marking	HA4
---------	-----




Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Rating	Unit
Maximum Repetitive Reverse Voltage	V_{RRM}	75	V
Breakdown Voltage	V_R	70	V
Average Rectified Forward Current	$I_{F(AV)}$	200	mA
Non-repetitive Peak Forward Surge Current	$I_{FSM(1)}$ (pulse width=1.0S)	1.0	A
	$I_{FSM(2)}$ (pulse width=1.0mS)	2.0	A
Power Dissipation	P_D	350	mW
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	357	°C/W
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	-55~150	°C


Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Breakdown Voltage	V_R	$I_R=100\mu A$	70			V
Forward Voltage	V_F	$I_F=1.0mA$			715	mV
		$I_F=10mA$			855	mV
		$I_F=50mA$			1.0	V
		$I_F=150mA$			1.25	V
Instantaneous Reverse Current	I_R	$V_R=70V$			5.0	μA
		$V_R=25V$ $T_A=150^\circ C$			60	μA
		$V_R=70V$ $T_A=150^\circ C$			100	μA
Total Capacitance	C_T	$V_R=0$ $f=1.0MHz$			1.5	pF
Reverse Recovery Time	t_{rr}	$I_F=I_R=10mA$ $I_{RR}=1.0mA$ $R_L=100\Omega$			6.0	ns

Electrical Characteristic Curve



Marking Instructions



Note:

H: Company Code.

A4: Product Type Code.

Packaging SPEC

REEL

Package Type	Units					Dimension (unit: mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOT-23	3,000	10	30,000	6	180,000	7" x8	180×120×180	390×385×205

Package Outline Dimensions

SOT-23

单位: mm

