

## Descriptions

This 20V 6.5A N-Channel MOSFET in a SOT-23 Plastic Package.


## Features

- Low  $R_{DS(ON)}$
- SOT-23 package
- Halogen-Free Product


## Applications

Battery management, High speed switch, low power DC to DC converter.

## Equivalent Circuit



## Pinning



PIN1: Gate      PIN 2: Source      PIN 3: Drain

## Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DS}$	20	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	V
Drain Current – Continuous	$I_D$	6.5	A
Pulsed Drain Current	$I_{DM}$	38	A
Power Dissipation	$P_D$	1.3	W
Storage Temperature Range	$T_{stg}$	-55~150	°C
Maximum Junction-to-Ambient	$t \leq 10s$	90	°C/W
Maximum Junction-to-Ambient	Steady-State	125	
Maximum Junction-to-Lead	Steady-State	80	

## Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	0.5	0.9	1.2	V
Drain–Source Breakdown Voltage	$V_{(BR)DS}$	$V_{GS}=0$ $I_D=250\mu A$	20	21		V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{GS}=0$ $V_{DS}=20V$			1.0	$\mu A$
Gate–Body Leakage.	$I_{GSS}$	$V_{GS}=\pm 12V$ $V_{DS}=0V$			$\pm 100$	nA
Static Drain–Source On–Resistance	$R_{DS(on)1}$	$V_{GS}=4.5V$ $I_D=5.0A$		16.5	33	m $\Omega$
	$R_{DS(on)2}$	$V_{GS}=2.5V$ $I_D=4.5A$		23.5	40	m $\Omega$
	$R_{DS(on)3}$	$V_{GS}=1.8V$ $I_D=4.0A$			51	m $\Omega$
Drain–Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V$ $I_D=1A$		0.78	1.2	V

## Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Input Capacitance	Ciss	$V_{GS}=0V, V_{DS}=10V$ $f=1MHz$		860		pF
Output Capacitance	Coss			800		
Reverse Transfer Capacitance	Crss			495		
Gate resistance	Rg	$V_{GS}=0V, V_{DS}=0V$ $f=1MHz$		4.9		$\Omega$
Total Gate Charge	Qg(4.5V)	$V_{GS}=4.5V, V_{DS}=10V$ $I_D=6.5A$		7		nC
Gate Source Charge	Qgs			1		
Gate Drain Charge	Qgd			2		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=4.5V, V_{DS}=10V$ $R_L=1.54\Omega, R_{GEN}=3\Omega$		7		ns
Turn-On Rise Time	$t_r$			10		
Turn-Off Delay Time	$t_{d(off)}$			32		
Turn-Off Fall Time	$t_f$			11		

Electrical Characteristic Curve




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area





Figure 10: Normalized Maximum Transient Thermal Impedance

## Marking Instructions



Note:

C2: Product Type Code

H: Company Code.

## Packaging SPEC

### REEL INFORMATION

Package Type	Units					Dimension (unit: mm <sup>3</sup> )		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOT-23	3,000	10	30,000	6	180,000	7" ×8	180×120×180	390×385×205

**Package Outline Dimensions**

SOT-23

单位: mm

