

Descriptions

This -30V -4.2A P-Channel MOSFET in a SOT23-3 Plastic Package.


Features

- V_{DS} (V) = -30V
- I_D = -4.2 A (V_{GS} = -10V)
- $R_{DS(ON)}$ < 60m Ω (V_{GS} = -10V)
- $R_{DS(ON)}$ < 65m Ω (V_{GS} = -4.5V)
- $R_{DS(ON)}$ < 120m Ω (V_{GS} = -2.5V)
- Halogen free product.

Applications

This device is suitable for use as a load switch or in PWM applications.

Equivalent Circuit



Pinning



PIN1: Gate PIN 2: Source PIN 3: Drain

Marking

Marking	B1H
---------	-----

Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	-30	V
Drain Current – Continuous	I_D	-4.2	A
Drain Current- Continuous ^A	$I_D(T_a=70^\circ\text{C})$	-3.5	A
Pulsed Drain Current ^B	I_{DM}	-30	A
Gate-Source Voltage	V_{GS}	± 12	V
Total Power Dissipation ^A	P_D	1.4	W
Total Power Dissipation ^A	$P_D(T_a=70^\circ\text{C})$	1.0	W
Operating and Storage Junction Temperature Range	T_J, T_{STG}	-55 to 150	°C
Maximum Junction-to-Ambient ^A	$R_{\theta JA}(T_a=70^\circ\text{C})$	125	°C/W
Maximum Junction-to-Lead ^C	$R_{\theta JL}$	60	°C/W

Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain–Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$ $I_D=-250\mu A$	-30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-24V$ $V_{GS}=0V$			-1	μA
		$V_{DS}=-24V$ $V_{GS}=0V$ $T_J=55^\circ\text{C}$			-5	μA
Gate–Body Leakage.	I_{GSS}	$V_{GS}=\pm 12V$ $V_{DS}=0V$			± 0.1	μA
On–State Drain Current	$I_{D(on)}$	$V_{GS}=-4.5V$ $V_{DS}=-5V$	-25			A
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=-250\mu A$	-0.7	-1	-1.3	V
Static Drain–Source On–Resistance	$R_{DS(on)(1)}$	$V_{GS}=-10V$ $I_D=-4.2A$		52	60	mΩ
	$R_{DS(on)(2)}$	$V_{GS}=-10V$ $I_D=-4.2A$ $T_J=125^\circ\text{C}$			75	
	$R_{DS(on)(3)}$	$V_{GS}=-4.5V$ $I_D=-4A$		60	65	
	$R_{DS(on)(4)}$	$V_{GS}=-2.5V$ $I_D=-1A$		75	120	
Forward Transconductance	g_{FS}	$V_{DS}=-5V$ $I_D=-5A$	4	8		S
Drain–Source Diode Forward Voltage	V_{SD}	$V_{GS}=0V$ $I_S=-1A$		-0.75	-1.0	V

Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Input Capacitance	C_{iss}	$V_{DS}=-15V \quad V_{GS}=0V$ $f=1MHz$		957		pF
Output Capacitance	C_{oss}			115		
Reverse Transfer Capacitance	C_{rss}			77		
Gate resistance	R_g	$V_{GS}=0V \quad V_{DS}=0V, f=1MHz$		6		Ω
Total Gate Charge	Q_g	$V_{GS}=-4.5V \quad V_{DS}=-15V$ $I_D=-4A$		9.4		nC
Gate Source Charge	Q_{gs}			2		
Gate Drain Charge	Q_{gd}			3		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=-10V \quad R_L=3.6\Omega$ $V_{DS}=-15V \quad R_{GEN}=6\Omega$		6.3		ns
Turn-On Rise Time	t_r			3.2		
Turn-Off Delay Time	$t_{d(off)}$			38.2		
Turn-Off Fall Time	t_f			12		
Body Diode Reverse Recovery Time	t_{rr}	$I_F=-4A, di/dt=100A/\mu s$		20.2		ns
Body Diode Reverse Recovery Charge	Q_{rr}	$I_F=-4A, di/dt=100A/\mu s$		11.2		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ C$. The value in any given application depends on the user's specific board design. The current rating is based on the $t \leq 10s$ thermal resistance rating.







B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.




D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80 μs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ C$. The SOA curve provides a single pulse rating.


Electrical Characteristic Curve



Electrical Characteristic Curve



Marking Instructions



Note:

B1: Product Type Code.

H: Company Code.

Packaging SPEC

REEL INFORMATION

Package Type	Units					Dimension (unit: mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOT23-3	3,000	10	30,000	4	120,000	7" x8	210×205×205	445×230×435

Package Outline Dimensions

