

## Descriptions

This 15A, 100V N-Channel MOSFET in a TO-252 Plastic Package.


## Features

- Low  $R_{DS(on)}$ ,
- Low gate charge,
- Low  $C_{iss}$ ,
- Fast switching.
- Halogen-free Product.

## Applications

Suited for low voltage applications such as automotive, DC/DC Converters, and high efficiency switching for power management in portable and battery operated products.

## Equivalent Circuit



## Pinning



PIN1: Gate    PIN 2: Drain    PIN 3: Source    PIN 4: Drain

## Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DSS}$	100	V
Drain Current	$I_D(T_C=25^\circ\text{C})$	15	A
Drain Current	$I_D(T_C=100^\circ\text{C})$	10	A
Drain Current - Pulsed*	$I_{DM}$	45	A
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Single Pulsed Avalanche Energy	$E_{AS}$	90	mJ
Avalanche Current	$I_{AS}$	9.1	A
Power Dissipation	$P_D(T_C=25^\circ\text{C})$	39	W
Operating and Storage Temperature Range	$T_j T_{stg}$	-55~150	°C
Junction-to-Ambient	$t \leq 10\text{s}$	20	°C/W
Junction-to-Ambient	Steady-State		
Junction-to-Case	Steady-State	3.2	

\*Repetitive rating; pulse width limited by max. junction temperature.

## Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Test Conditions	Min	Type	Max	Unit
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V$ $I_D=250\mu A$	100			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=100V$ $V_{GS}=0V$			1.0	$\mu A$
		$T_J=125^\circ C$			50	
Gate-Body Leakage Current Forward	$I_{GSS}$	$V_{GS}=\pm 20V$ $V_{DS}=0V$			$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	1	1.9	3	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=8.5A$		75	90	m $\Omega$
		$T_J=125^\circ C$		142		
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V$ $I_S=15A$		1.0	1.2	V
Gate resistance	$R_g$	$V_{GS}=0V$ $V_{DS}=0V$ $f=1MHz$		1.3		$\Omega$
Input Capacitance	$C_{iss}$	$V_{DS}=25V$ $V_{GS}=0V$ $f=1.0MHz$		250		pF
Output Capacitance	$C_{oss}$			125		pF
Reverse Transfer Capacitance	$C_{rss}$			20		pF
Total Gate Charge(10V)	$Q_g$				5.8	
Total Gate Charge(4.5V)	$Q_g$	$V_{GS}=10V$ $V_{DS}=50V$ $I_D=5A$		2.8		nC
Gate Source Charge	$Q_{gs}$			1.1		nC
Gate Drain Charge	$Q_{gd}$			1.2		nC
Turn-On Delay Time	$t_{d(on)}$				6	
Turn-On Rise Time	$t_r$	$V_{GS}=10V$ $V_{DS}=50V$ $R_L=10\Omega$ $R_{GEN}=3\Omega$		2.5		ns
Turn-Off Delay Time	$t_{d(off)}$			18		ns
Turn-Off Fall Time	$t_f$			2.5		ns

Electrical Characteristic Curve




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area





Figure 10 : Normalized Maximum Transient Thermal Impedance

**Marking Instructions**



Note:

COT: Company Logo

15N10: Product Type.

\*\*\*\*: Lot No. Code, code change with Lot No.

**Packaging SPEC**


**REEL INFORMATION**

Package Type	Units					Dimension (unit: mm <sup>3</sup> )		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
TO-252	2,500	2	5,000	6	30,000	13" x16	360x360x50	380x335x366

**TUBE INFORMATION**

Package Type	Units					Dimension (unit: mm <sup>3</sup> )		
	Units/Tube	Tubes/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Tube	Inner Box	Outer Box
TO-252	75	48	3,600	5	18,000	526x20.5x5.25	555x164x50	575x290x180

Package Outline Dimensions



单位: mm

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
A	2.20	2.40	E	5.95	6.25
B	0.95	1.25	e1	2.24	2.34
b	0.70	0.90	e2	4.43	4.73
b1	0.45	0.55	L1	9.85	10.35
C	0.45	0.55	L2	1.70	2.00
D	6.45	6.75	L3	0.60	0.90
D1	5.10	5.50	K	0.00	0.10

TO-252