

## Descriptions

This 100V, 68A N-Channel MOSFET in a TO-252 Plastic Package.


## Features

- Low RDS(on)
- Low gate charge
- Low  $C_{rss}$
- Fast switching
- HF Product.


## Applications

- Suited for low voltage applications such as automotive.
- DC/DC Converters
- and high efficiency switching for power management in portable and battery operated products
- Meet the stringent requirements of automotive applications

## Equivalent Circuit



## Pinning



PIN1: G    PIN 2: D    PIN 3: S    PIN 4: D

**Absolute Maximum Ratings(Ta=25°C)**

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DS}$	100	V
Drain Current - Continuous	$I_D$	68	A
Drain Current – Pulsed	$I_{DM}$	156	A
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Power Dissipation	$P_D(T_c=25^\circ C)$	75	W
Single Pulse Avalanche Energy(L=0.5mH)	$E_{AS}$	119	mJ
Avalanche Current(L=0.5mH)	$I_{AS}$	18.5	A
Junction and Storage Temperature Range	$T_j, T_{stg}$	-55 to 150	°C
Thermal resistance, junction - ambient	$t \leq 10s$	$R_{\theta JA}$	°C/ W
	Steady-State		
Thermal resistance, junction - case	Steady-State	$R_{\theta JC}$	1.7

**Electrical Characteristics(Ta=25°C)**

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V \quad I_D=250\mu A$	100	109		V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=100V \quad V_{GS}=0V$			1.0	$\mu A$
Gate-Body Leakage Current Forward	$I_{GSS}$	$V_{GS}=\pm 20V \quad V_{DS}=0V$			$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS} \quad I_D=250\mu A$	2	2.9	4	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V \quad I_D=30A$		7	8	m $\Omega$
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V \quad I_S=1A$			1.2	V
Gate resistance	$R_g$	$V_{GS}=0V \quad V_{DS}=0V, \quad f=1MHz$		3.1		$\Omega$
Input Capacitance	$C_{iss}$	$V_{DS}=25V \quad V_{GS}=0V \quad f=1.0MHz$		2500		pF
Output Capacitance	$C_{oss}$			1250		
Reverse Transfer Capacitance	$C_{rss}$			110		
Total Gate Charge	$Q_g$	$V_{GS}=10V, \quad V_{DS}=50V, \quad I_D=20A$		25		nC
Gate Source Charge	$Q_{gs}$			6		
Gate Drain Charge	$Q_{gd}$			3.5		

## Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=50V$ $R_L=2.5$ $R_{GEN}=3 \Omega$		8.5		ns
Turn-On Rise Time	$t_r$			3		
Turn-Off Delay Time	$t_{d(off)}$			23		
Turn-Off Fall Time	$t_f$			3.5		

Electrical Characteristic Curve




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area




Figure 10: Maximum Continuous Drain Current Vs Case Temperature




Figure 11: Normalized Maximum Transient Thermal Impedance

**Marking Instructions**



Note:

COT: Company Logo

080N10SH: Product Type.

\*\*\*\*: Lot No. Code, code change with Lot No.

**Packaging SPEC**


REEL INFORMATION

Package Type	Units					Dimension (unit: mm <sup>3</sup> )		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
TO-252	2,500	2	5,000	6	30,000	13" x16	360×360×50	380×335×366

TUBE INFORMATION

Package Type	Units					Dimension (unit: mm <sup>3</sup> )		
	Units/Tube	Tubes/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Tube	Inner Box	Outer Box
TO-252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

Package Outline Dimensions



单位: mm

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
A	2.20	2.40	E	5.95	6.25
B	0.95	1.25	e1	2.24	2.34
b	0.70	0.90	e2	4.43	4.73
b1	0.45	0.55	L1	9.85	10.35
C	0.45	0.55	L2	1.70	2.00
D	6.45	6.75	L3	0.60	0.90
D1	5.10	5.50	K	0.00	0.10

TO-252