

Descriptions

This 60V 70A, N-CHANNEL MOSFET in a TO-252 Plastic Package.



Features

- Low RDS(on)
- Low gate charge
- Low Crss
- Fast switching
- Halogen-free Product

Applications

- Suited for low voltage applications such as automotive.
- DC/DC Converters.
- High efficiency switching for power management in portable and battery operated products.

Equivalent Circuit & Pinning



PIN1: G PIN 2: D PIN 3: S PIN 4: D

Marking

See Marking Instructions

Absolute Maximum Ratings(Ta=25°C)

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DSS}	60	V
Drain Current		$I_D(T_C=25^\circ C)$	70	A
Drain Current - Pulsed		I_{DM}	280	A
Gate-Source Voltage		V_{GS}	± 20	V
Avalanche Current		I_{AS}	44	A
Single Pulsed Avalanche Energy(L=0.5mH)		E_{AS}	677.6	mJ
Power Dissipation		$P_D(T_C=25^\circ C)$	113	W
Storage Temperature Range		T_{stg}	-55~150	°C
Thermal Resistance-Junction to Ambient	t≤10s	$R_{\theta JA}$	20	°C/W
	Steady-State		50	
Thermal Resistance-Junction to Case	Steady-State	$R_{\theta JC}$	1.1	

Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$ $I_D=250\mu A$	60	68		V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=60V$ $V_{GS}=0V$			1.0	μA
		$V_{DS}=48V$ $T_C=150^\circ C$			10	
Gate-Body Leakage Current Forward	I_{GSS}	$V_{GS}=\pm 20V$ $V_{DS}=0V$			± 0.1	μA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	1.0	1.6	2.5	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=20A$		2.9	3.5	mΩ
		$V_{GS}=4.5V$ $I_D=10A$		3.7	5.0	
Drain-Source Diode Forward Voltage	V_{SD}	$V_{GS}=0V$ $I_S=1A$			1.2	V
Gate resistance	R_g	$V_{GS}=0V$ $V_{DS}=0V$, f=1MHz		1.0		Ω
Input Capacitance	C_{iss}	$V_{DS}=25V$ $V_{GS}=0V$ f=1.0MHz		3450		pF
Output Capacitance	C_{oss}			1700		
Reverse Transfer Capacitance	C_{rss}			100		
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=10V$, $V_{DS}=30V$, $I_D=20A$		60		nC
Total Gate Charge	$Q_{g(4.5V)}$			23		
Gate Source Charge	Q_{gs}			16		
Gate Drain Charge	Q_{gd}			3		

Electrical Characteristics(Ta=25°C)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=30V$ $R_L=1.5\Omega$ $R_{GEN}=3\Omega$		13		ns
Turn-On Rise Time	t_r			4		
Turn-Off Delay Time	$t_{d(off)}$			47		
Turn-Off Fall Time	t_f			6.5		

Electrical Characteristic Curve




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

Electrical Characteristic Curve




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs Case Temperature




Figure 11: Normalized Maximum Transient Thermal Impedance

Marking Instructions



Note:

COT: Company Logo

035N06S: Product Type.

****: Lot No. Code, code change with Lot No.

Packaging SPEC


REEL INFORMATION

Package Type	Units					Dimension (unit: mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
TO-252	2,500	2	5,000	6	30,000	13" ×16	360×360×50	380×335×366

TUBE INFORMATION

Package Type	Units					Dimension (unit: mm ³)		
	Units/Tube	Tubes/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Tube	Inner Box	Outer Box
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

Package Outline Dimensions



单位: mm

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
A	2.20	2.40	E	5.95	6.25
B	0.95	1.25	e1	2.24	2.34
b	0.70	0.90	e2	4.43	4.73
b1	0.45	0.55	L1	9.85	10.35
C	0.45	0.55	L2	1.70	2.00
D	6.45	6.75	L3	0.60	0.90
D1	5.10	5.50	K	0.00	0.10

TO-252